Digital TV Converter Box Certified for NTIA \$40 Coupon Program



| Operation | 120VAC, 60Hz, 12W max. |
|------------|-------------------------|
| | |
| Standby | <2W |
| | |
| Dimensions | 227.9 x 133.5 x 45.6 mm |

Weight 1.73 lb.

Features

- Capable of passing analog signals through to the TV set.
- Receiving RF channels 2 through 69 inclusive.
- MPEG-2 Digital & Fully ATSC Compliant for all 18 ATSC broadcast formats, contained in ATSC A/53E.
- Selectable picture aspect ratios for 4:3 and 16:9 TV screen.
- Channel Auto search, channel add, channel skip and favorite channel setting functions.
- I-Plate design allows users to view tuned channel and program information.
- Include the RF IN Female-type connector for VHF/ UHF antenna input and RF OUT connector for CH3/CH4 selectable RF output.
- High quality Composite output provided.
- Closed Captioning and Emergency Alert System support.
- Parental Control with V-Chip technology
- Advanced Parental Lock function with downloadable Rating Region table.
- On-screen trilingual (English, French and Spanish) menu display
- ATSC Dolby AC-3 audio decoding
- Fully complaint with Energy Star Standards.

PRODUCT SPECIFICATIONS

| R | F Input |
|-----------------|------------|
| Demodulation | 8VSB |
| Frequency Range | 54-860 MHz |
| Connector | F-Type x 1 |

RF Output

| Signal Type | NTSC |
|----------------|----------------------|
| | |
| Output Channel | CH3 / CH4 selectable |
| | |
| Connector | F-Type x 1 |

Video Output

| Signal Type | NTSC |
|--------------|---------|
| Impedance | 75 Ω |
| Output Level | 1 Vp-p |
| Connectors | RCA x 1 |

Audio Output

| Output | Left & Right channel |
|--------------|------------------------|
| Impedance | 600Ω max |
| Output Level | 2Vrms +-10%@0dBFS |
| Connectors | RCA x 2 (Left & Right) |

Front Panel

IR Receiver

3 Keys Function Control

Status LED (Power and standby)

Remote Control

26 Keys Remote Control

*Specifications are subject to change without notice.

With analog pass through feature



| External power adaptor | | | | | |
|------------------------|-------------------------|--|--|--|--|
| Operation | 120VAC, 60Hz, 4.5W max. | | | | |
| Standby | <1.3W | | | | |
| Dimensions | 175 x 135 x 33 mm | | | | |

Weight 0.98 lb.









